



7061

BEAM POWER TUBE

9-PIN MINIATURE TYPE

For use in mobile communications equipment
operating from 6-cell storage-battery systems

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage range. 12 to 15 ac or dc volts
Current (Approx.) at
13.5 volts 0.21 amp


Direct Interelectrode Capacitances:⁰

Grid No.1 to plate 0.7 max. μ f
Grid No.1 to all other electrodes
except plate 8 μ f
Plate to all other electrodes
except grid No.1 8.5 μ f

Mechanical:

Operating Position Any
Maximum Overall Length 2-5/8"
Maximum Seated Length 2-3/8"
Length, Base Seat to Bulb Top (Excluding tip). . . 2" \pm 3/32"
Diameter 0.750" to 0.875"
Dimensional Outline. See General Section
Bulb T6-1/2
Base Small-Button Noval 9-Pin (JETEC No.E9-1)
Basing Designation for BOTTOM VIEW 9EU

Pin 1-Grid No.2
Pin 2-No Con-
nection
Pin 3-Grid No.1
Pin 4-Heater
Pin 5-Heater



Pin 6-Grid No.1
Pin 7-Cathode,
Grid No.3
Pin 8-Grid No.2
Pin 9-Plate

AMPLIFIER — Class A₁

Maximum Ratings, Absolute Values:

PLATE VOLTAGE 345 max. volts
GRID-No.2 (SCREEN-GRID) VOLTAGE 310 max. volts
GRID-No.2 INPUT 2 max. watts
PLATE DISSIPATION 9 max. watts
PEAK HEATER-CATHODE VOLTAGE:
Heater negative with respect to cathode 120 max. volts
Heater positive with respect to cathode 120 max. volts

Typical Operation and Characteristics:

Heater Voltage. 13.5 volts
Plate Voltage 200 volts
Grid-No.2 Voltage 200 volts
Grid-No.1 (Control-Grid) Voltage. -10 volts

⁰ Without external shield.

11-58

ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

TENTATIVE DATA 1

7061



7061

BEAM POWER TUBE

Peak AF Grid-No.1 Voltage	10	volts
Zero-Signal Plate Current	35.5	ma
Max.-Signal Plate Current	38	ma
Zero-Signal Grid-No.2 Current	9	ma
Max.-Signal Grid-No.2 Current	7.5	ma
Plate Resistance (Approx.)	60000	ohms
Transconductance	4200	μ mhos
Load Resistance	5000	ohms
Total Harmonic Distortion	7	%
Max.-Signal Power Output	3	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1 max.	megohm
For cathode-bias operation	0.5 max.	megohm

CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

	Note	Min.	Max.	
Heater Current	1	0.19	0.23	amp
Transconductance	1,2	3100	5800	μ mhos
Plate Current	1,2	26	45	ma
Grid-No.2 Current	1,2	-	6.5	ma
Reverse Grid-No.1 Current	1,3	-	-2	μ a
Power Output	1,4	2.4	-	watts
Heater-Cathode Leakage Current:				
Heater negative with respect to cathode	1,5	-	50	μ a
Heater positive with respect to cathode	1,5	-	50	μ a
Leakage Resistance:				
Between grid No.1 and all other electrodes tied together	1,6	50	-	megohms
Between plate and all other electrodes tied together	1,7	50	-	megohms

Note 1: With ac or dc heater volts = 13.5.

Note 2: With dc plate volts = 200, grid-No.2 volts = 200, grid-No.1 volts = -10, and grid No.3 connected to cathode.

Note 3: With grid-No.1 resistor (megohms) = 0.1.

Note 4: With load resistor (ohms) = 5000, and rms signal volts = 7.1.

Note 5: With 100 volts dc between heater and cathode.

Note 6: With grid No.1 100 volts negative with respect to all other electrodes tied together.

Note 7: With plate 300 volts negative with respect to all other electrodes tied together.

SPECIAL RATINGS & PERFORMANCE DATA

Heater-Cycling Life Performance:

This test is performed on a sample lot of tubes from each production run. A minimum of 2000 cycles of intermittent



7061

7061

BEAM POWER TUBE

operation is applied under the following conditions: heater volts = 17 cycled one minute on and four minutes off, heater 135 volts negative with respect to cathode, and all other elements connected to ground. At the end of this test, tubes are checked for heater-cathode shorts and open circuits.

Low-Frequency Vibration Performance:

This test is performed on a sample lot of tubes from each production run under the following conditions: heater volts = 13.5, plate volts = 200, grid-No.2 volts = 200, grid-No.1 volts = -10, plate load resistor (ohms) = 2000, and vibrational acceleration of 2.5 g at 25 cps. In this test, the rms output voltage must not exceed 500 millivolts.

500-Hour Intermittent Life Performance:


This test is performed on a sample lot of tubes from each production run to insure high quality of the individual tube and to guard against epidemic failures. Life testing is conducted under the following conditions: heater volts = 15, and maximum-rated plate dissipation and grid-No.2 input.

7061



7061

AVERAGE CHARACTERISTICS



ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-9802



7061

7061

AVERAGE CHARACTERISTICS



ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-9794

7061



7061

OPERATION CHARACTERISTICS



ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-9814



7061

AVERAGE CHARACTERISTICS TRIODE CONNECTION

7061



ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-9801